



CIRCUIT DIAGRAM—COSSOR MELODY MAKER MODEL 494

Capacitors.

- C1 0.005
- C2 5-60 pF.
- C3 75 pF.
- C4 5-60 pF.
- C5 Main tuning
- C6 500 pF.
- C7 100 pF.
- C8 100 pF.
- C9 100 pF.
- C10 Main tuning
- C11 5-60 pF.
- C12 440 pF.
- C13 5-60 pF.
- C14 133 pF.
- C15 500 pF.
- C16 0.1
- C17 5-60 pF.
- C18 0.1
- C19 100 pF.
- C20 100 pF.
- C21 100 pF.
- C22 100 pF.
- C23 0.005
- C24 32 (450 v.)
- C25 0.02
- C26 0.01
- C27 100 pF.
- C28 0.005
- C29 25 (25 v.)
- C30 16 (450 v.)

Resistors.

- R1 1000
- R2 330k
- R3 47k
- R4 33k
- R5 2.2M
- R6 12k
- R7 47k
- R8 0.5M
- R9 4.7M
- R10 1 W.
- R11 1 W.
- R12 1 W.
- R13 1 W.
- R14 1 W.
- R15 1 W.
- R16 1 W.
- R17 Pot.
- R18 680k
- R19 100
- R20 0.5M
- R21 470
- R22 470k
- R23 47k
- R24 2.7k
- R25 270
- R26 1 W.
- R27 Pot.
- R28 1 W.
- R29 1 W.
- R30 1 W.

Approx. D.C. Resistances.

- L3 3.5
- L4 13.5
- L5 9
- L6 9
- L8 2.6
- L9 2.8
- L10 7.5
- L11 5.5
- L12 9
- L13 9
- L14 13
- T1 (p) 280
- T2 (p) 47 (Total)
- T2 (s) 265 + 265
- L1, L2, L7 Very low

